

X-Factor Series FESLX

Ironsoft Water Softener

Homeowner Benefits

- The electronic control valve with demand initiated or time clock initiated regeneration allows the dealer to precisely predict the use and installation of the proper system to achieve the desired results for the homeowner
- In addition to softening hard water, Ironsoft removes iron in both clear water and red water conditions
- Available in the space-saving cabinet model or the two-tank model
- Multiple applications in capacity from 24,000 to 64,000 grains assuring system will be sized to meet the water treatment needs of the household
- An authorized water treatment dealer who understands your application and installation requirements
- Family members will all experience improvements of treated water after installation



Series Overview

A real breakthrough in water treatment equipment, Lancaster's "Ironsoft" will not only soften hard water, but will remove up to 10 ppm of Ferrous (clear water) iron and/or Ferric (red water) iron.

Our "Ironsoft" family of high-performance microprocessor control valves provides the ultimate in system capabilities and water treatment benefits. These dependable and easy-to-install units assure the dealer and homeowner that the system will perform reliably.

Operating with a fine mesh resin, which has a smaller bead size than standard resin, this unit is much more efficient in grains exchange capacity and is also a much better filter than standard units. The specially designed support bed media acts as a secondary filter.

Backwash rates on the "Ironsoft" are a fraction of the requirements of ordinary iron filters, which allows the use of the "Ironsoft" on relatively poor producing wells.

Additionally, "Ironsoft" is not sensitive to pH and can be operated in acidic water, which would not be compatible with an ordinary iron filter.

Periodic regeneration with water softener salt is required and the use of resin cleaner is recommended for maximum resin efficiency. Available in a two-tank model or the space-saving cabinet style.



X-Factor Series FESLX

Ironsoft Water Softener



Lancaster Designed State-of-the-Art Control Valve

- Factory-set pre-fill brine
- Dot matrix display
- Scrolling text display
- Contractor contact screens
- Additional user display choices during normal service
- Color specific display: Solid Blue, In Service; Solid Green, In Regeneration; Flashing Yellow, Maintenance; Flashing Red, Error.
- Water drop flow indicator
- Contractor service call reminder
- Display and keypad backlight illumination
- Screen displays low battery when the backup battery needs replaced
- Two relay driver outputs
- Multiple regenerations per day
- Additional diagnostics information
- Additional valve history information
- DC battery operation available
- Monitors water consumption, water flow rates, gallons since last regeneration, days between regeneration, total regenerations since start-up
- Treated water brine refill
- Easy-access front panel settings
- Days override feature: 1-28 days available
- Stores system configuration and operation data in a nonvolatile memory
- Valve ported internally 1"
- Battery back-up with up to 8 hours power carry-over

Ironsoft Electronic Series

Uses fine mesh resin, (smaller bead-size) for more efficient grains exchange capacity and better filtration. Removes up to 10 ppm of ferrous (clear water) iron and/or ferric (red water) iron. Backwash rates on Ironsoft are a fraction of the requirement of ordinary iron filters, which allows the use of the Ironsoft on relatively poor producing wells. Solid-state microprocessor based LCD control valve.

Why Buy?

Iron is highly objectionable. It imparts a metallic taste to water. Much worse, it stains practically everything with which it comes in contact. Iron bearing water is usually clear and colorless with dissolved ferrous iron. Exposure to air causes it to oxidize to ferric iron, cloud up and deposit a yellowish or reddish-brown sediment of ferric hydroxide. Ferric hydroxide causes staining. Manganese can accompany iron, producing objectionable dark brown or black stains.

Water softeners remove unwanted hardness and minerals from your household water - whether from private well or municipal source. Water softeners in combination with filters, neutralizers and reverse osmosis systems can meet the most challenging water problems.



Cabinet

- Cabinet design offers space saving by combining the mineral tank and brine tank into one unit that allows up to 225LBS. of salt storage.

Easy to Program

- Set time of day
- Set water hardness
- Set desired time of regeneration
- Set contractor name and phone number



TWO TANK					CABINET
MODEL NO.	7-FESLX-24	7-FESLX-32	7-FESLX-45	7-FESLX-60	7-FESLXC-24
Grains Capacity Max	24,000	32,000	48,000	64,000	24,000
Mineral Tank Size (in.)	8x44	10x47	12x48	13x48	10x35
Brine Tank Size (in.)	18x33	18x33	18x33	18x40	14x23x44*
Brine Tank Capacity (lbs.)	375	375	375	450	225
LBS NaCl Per Regeneration	11.3	15.0	22.5	30.0	11.3
Service Flow Rate (gpm)**	13	17	18	19	18
Backwash Rate (gpm)	0.7	1.3	1.3	1.3	1.3
Pipe Size (in.)	1	1	1	1	1
Operating Pressure (psi) min.-max.	20-100	20-100	20-100	20-100	20-100
Operating Temperature (°F) min.-max.	35-100	35-100	35-100	35-100	35-100

*Includes cabinet cover **At 15 psi pressure drop



1340 Manheim Pike, Lancaster, PA 17601 Phone: 717-397-3521 Fax: 717-392-0266

www.lancasterwatertreatment.com

"Copyright 2010 Lancaster Pump and Water Treatment All Rights Reserved."