

Commercial WF-15CC Filters & Neutralizers



LANCASTER'S Commercial Water Filters & Neutralizers, utilizing the WF15CC 1-1/2" Brass Filter Control Valve, are capable of handling peak flows with a limited pressure loss. The top mount control valve is available with a 1 to 28 day time clock. The following commercial water filters and neutralizers are available to satisfy your every need from pH correction to improving the taste of your water.

Acid Neutralizers

Model: AN Mineral: Calcite

Acid Neutralizers correct low pH water which in turn protects your pipes, heaters, boilers and appliances requiring the use of water. Periodic replacement of the consumed calcite is required.

Note: Calcite is recommended for a pH of 6.0 or higher. If lower than 6.0, use calcite/corosex (super mix), if lower than 5.0, use a chemical feed pump and soda ash.

Iron Filters

Model: IM Mineral: Birm

Iron Filters remove iron and manganese, prevent rust stains on your clothing and enamel and will remove the taste and color of iron. These units are supplied with the mineral birm which requires no chemical regeneration, but does demand a pH of 7.0 or higher.

Note: Dissolved Oxygen (D.O.) content must be equal to at least 15% of the iron (or iron and manganese) content.

Color, Taste & Odor Filters

Model: CT Mineral: Hi-activated Carbon

Carbon filters remove chlorine, sulphur, mold, fishy, muddy and so-called swamp taste and odors while giving your water a high polish. Mineral must be replaced when maximum adsorbency has been reached.

Sediment & Turbidity Filters

Model: ST Mineral: Filter Ag

Sediment Filters remove dirt, silica and most suspended matter from your water supply. When using this filter, it should be placed before any filter or softener if suspended matter could interfere with the performance of your equipment.



MODEL NUMBER ³	SERVICE FLOW RATES		BACK-WASH GPM (DLFC)	MINERAL TANK DIA x HT INCHES	OVERALL HEIGHT INCHES	MINERAL VOLUME CU. FT.
	CONTINUOUS ¹	INTERMITTENT ²				
	GPM	GPM				
7-WF15-4	7.0	14.0	15.0	16 x 65	78	4
7-WF15-7	12.0	24.0	25.0	21 x 62	75	7
7-WF15-10	16.0	31.0	30.0	24 x 71	84	10

1: Based on 5 gpm/ft²

2: Based on 10 gpm/ft²

3: Typical Model Numbers: 7-WF15AN-4, 7-WF15IM-4, 7-WF15CT-4, 7-WF15ST-4



1340 Manheim Pike, Lancaster, PA 17601 Phone: 717-397-3521 Fax: 717-392-0266

www.lancasterwatertreatment.com

"Copyright 2008 Lancaster Pump and Water Treatment All Rights Reserved."